

www.wic-ltd.com Phone: +44 1922 722933 wic@wic-ltd.com

Toroidal Transformer - Open

Standard open toroidal transformer, Primary 2x 115 VAC and 2 secondaries

Standard toroidal transformers designed according to the following specifications.

- High quality safety and isolating transformers designed for use in control circuits and general applications
- Very good quality, low loss and noise toroidal core
- Dual standard primary winding 2x 115 VAC
- In series connection the transformer can be supplied by 230 VAC
- In parallel connection the transformer can be supplied by 115 VAC
- Dual secondary windings
- Detailed product specification on permanent label
- High efficiency, low regulation design
- Environmentally friendly, low energy dissipation
- 100% electrical and flash tested



Specifications

Power: 15 - 3500 VA Frequency: 50/60 Hz Primary: 2x 115 VAC (two separate windings) Secondary: 2x (6, 9, 12, 15, 18, 24, 30, 40, 45, 50, 55, 115) VAC Isolation: 4 kV RMS Temp. rise: 55° Temp. class: A (105°) According to: EN61558-2-4, Marking: UL and CE Approval: UL 506, UL60601-1

Technical specification				
Power	Secondary voltages	Overall Size	Weight	
[VA]	[V]	OD x ID x H [mm]	[kg]	
15	2x (6, 9, 12, 15, 18, 24)	60 x 20 x 28	0.27	
30	2x (6, 9, 12, 15, 18, 24)	70 x 25 x 32	0.45	
50	2x (9, 12, 15, 18, 24, 55)	80 x 30 x 34	0.65	
80	2x (9, 12, 15, 18, 24, 55)	90 x 35 x 36	0.90	
100	2x (9, 12, 15, 18, 24, 55)	90 x 37 x 42	1.10	
120	2x (12, 15, 18, 24, 55)	90 x 37 x 48	1.30	
160	2x (12, 15, 18, 24, 55)	100 x 35 x 45	1.55	
200	2x (12, 15, 18, 24, 55, 115)	115 x 40 x 45	1.90	
250	2x (24, 30, 40, 45, 50, 55, 115)	115 x 40 x 52	2.40	
300	2x (24, 30, 40, 45, 50, 55, 115)	117 x 40 x 60	2.70	
400	2x (24, 30, 40, 45, 50, 55, 115)	130 x 40 x 55	3.35	
500	2x (24, 30, 40, 45, 50, 55, 115)	135 x 50 x 68	4.00	
800	2x (24, 30, 45, 50, 55, 115)	160 x 58 x 78	6.40	

>

Walsall Inductive Components Ltd · T3 Four · Tameway Tower · 48 Bridge Street · Walsall · West Midlands · WS1 1JZ · United Kingdom Company No.: 6562151 · VAT: 931640343 Member of Scandinavian Transformer Group



1000	2x (24, 30, 45, 50, 55, 115)	172 x 70 x 85	8.40
1500	2x (45, 50, 55, 115)	172 x 65 x 90	9.60
2000	2x (50, 55, 115)	238 x 90 x 75	13.00
2500	2x (50, 55, 115)	245 x 80 x 85	15.00
3000	2x (50, 55, 115)	240 x 85 x 105	20.50
3500	2x (50, 55, 115)	240 x 80 x 105	22.00